

Model	Catalog Number	Cal.	Total Wt.	Overall Length	Velocity fps	Muzzle Energy	Accuracy c-t-c	Cocking Method	Cocking Effort	Powerplant	Rifling (Grooves)	Stock	Trigger	Safety
R1	11010 (Rt) 11011 (Lt)	.177	8.8 lbs.	45.2"	950	14.23 FP	0.15"	Break Barrel	34 lbs.	Spring Piston	12	Beech Stained	Two-Stage Adjustable	Automatic
R1 Carbine	11010C (Rt) 1011C (Lt)	.177	8.3 lbs.	42.0"	950	14.23 FP	0.15"	Break Barrel	42 lbs.	Spring Piston	12	Beech Stained	Two-Stage Adjustable	Automatic
R1	11015 (Rt) 1016 (Lt)	.20	8.8 lbs.	45.2"	860	15.1 FP	0.19"	Break Barrel	34 lbs.	Spring Piston	12	Beech Stained	Two-Stage Adjustable	Automatic
R1 Carbine	1015C (Rt) 1016C (Lt)	.20	8.3 lbs.	42.0"	860	15.1 FP	0.19"	Break Barrel	42 lbs.	Spring Piston	12	Beech Stained	Two-Stage Adjustable	Automatic
R1	1012 (Rt) 1013 (Lt)	.22	8.7 lbs.	45.2"	765	16.4 FP	0.21"	Break Barrel	34 lbs.	Spring Piston	6	Beech Stained	Two-Stage Adjustable	Automatic
R1 Carbine	1012C (Rt) 1013C (Lt)	.22	8.3 lbs.	42"	765	16.4 FP	0.21"	Break Barrel	42 lbs.	Spring Piston	6	Beech Stained	Two-Stage Adjustable	Automatic